



# Plastic drawing .. Deep drawing

# Mobile Vacuum Pomp. No OIL VP.30 VP.40

External Vacuum-Unit- suitable for mobile purposes as well

Suction speeds demanded by manufacturers of modern thermoplastics for optimum processing can be realized with this vacuum aggregate. It comprises a maintenance-free vacuum pump mounted along with the control electronics and a vacuum-gauge in a convenient and easy to transport housing.

### **Technical Data**

Product Code Dimensions Capacity Power Supply Weight Net Boxed : Dimension and Total Weight

Product Code Dimensions Capacity Power Supply Vacuum Accessories

Weight Net Boxed : Dimension and Total Weight

## Descriptions

VP.30 W.400 D.200 H.250 mm 2.5 m3/200 mbar 220 Volt 50 HZ 136 watt 7 Kg W.40 -D.40- H.40 cm 8,5 kg

#### VP.40

W.400 D.200 H.250 mm 4m3/200 mbar 220 Volt 50 HZ 136 watt 1 Separate İnlets (No Setting) Weight 12 kg 1 Pcs Hose 5 mt + 1 Pcs Filter 1 Pcs water collection container 12 Kg W.50 -D.500- H.60 cm 15 kg

Page.8

www,ortomak.com ortomak@ortomak.com